

pE-4000

Flexible
Microscopy
Illumination




pE-4000


Flexible Microscopy Illumination

Selectability

- Choice of 256 wavelength combinations from 16 installed LEDs (365nm-770nm)
- Choose 1 of 4 wavelengths for each of 4 channels on the control pod
- Unique wavelength grouping concept
- Optimum wavelength to suit your experiment
- Specific wavelength characterisation for optimal optogenetic control of cell responses



DAPI/FITC/TRITC/Cy5 Quad filter excited by pE-4000 at matched wavelengths shown above



The pE-4000 allows multiple experiments with varying wavelengths on the same sample, as shown here.

(A) Representative photocurrent traces of a PhobosCA expressing CA1 cell evoked with different activation wavelengths and shutoff with 595 nm light.

(B) Photocurrent traces in the same cell evoked with 460 nm light and shutoff with indicated wavelengths (10 mW/mm²).

Wietek J et al (2017) Anion-conducting channelrhodopsins with tuned spectra and modified kinetics engineered for optogenetic manipulation of behaviour. Scientific Reports volume 7, Article number: 14957(2017) doi:10.1038/s41598-017-14330-y

Sustainability

Power Consumption	
Standby (no LEDs on)	Max 7W
Single wavelength	Max 25W
Dual wavelength	Max 44W
Triple wavelength	Max 53W
Quad wavelength	Max 60W

- Lowest power consumption - other LED technology uses 120W to 350W
- >25000 hours operation
- Highly stable, repeatable award-winning single chip LED technology
- Market leading energy efficiency

Cell Viability

- Optimal illumination through control features to extend fluorescence of cells
- Reduced photobleaching and phototoxicity
- Microsecond switching
- Variable pulse duration on/off

"When you can only control intensity of 'white' light (rather than individual channels), the level of photobleaching can be high. With the pE-4000, we can control the excitation of the individual channels. It is possible to optimise the excitation intensity according to the labelling, greatly reducing photobleaching and phototoxicity in a live experiment."

Dr. Yan Gu,
University of Sussex

"Suddenly we were able to offer users uninterrupted extended live cell experiments of 100+ hours, without worrying about brightness fluctuations, lamps burning, room heating, etc. Also, users have reported markedly reduced bleaching and phototoxicity in their samples, both from the prokaryotic and the eukaryotic research fields"

Dr. Jens Eriksson,
Oslo University Hospital



Pod functions: Presets, white light and intensity control



pE-Universal Collimator




Removable inline excitation filter holders

Controllability

- Advanced integration into major microscope software platforms
- Save wavelength combinations and return to previous set-up
- USB interface
- High Speed TTL triggering
- Analogue control - dynamic intensity sinusoidal control option
- White light control
- Expansion box
- Individual channel intensity control
- Pre-determined intensity saving option



pE-4000 Expansion Box




Visibility

- High signal to noise ratio which gives cleaner images and data

"Striking, bright fluorescence images with a strong signal to noise ratio even when using a low magnification objective"

Graham Wright, Institute of Medical Biology, A*STAR, Singapore



Time series of a confluent sheet of keratinocytes migrating during a live-cell imaging outgrowth assay, acquired on an Olympus IX-83 microscope equipped with a CoolLED pE-4000 Illumination System (Fig. 4). Scale bar = 150 μ m. Institute of Medical Biology, A*STAR, Singapore

Reliability

- Assured through experience and QA assured processes
- 3 year Warranty after registration
- First year Warranty swap



Specification

pE-4000 illumination system:	Light source with complete set of wavelengths, manual control pod, and power supply
Light delivery:	Single liquid light guide or fiber options
Collimating optics:	pE-Universal Collimator for use with a liquid light guide. Requires microscope adaptor
LED wavelengths:	LED wavelengths are divided across 4 channels with each channel having individual control

Due to a programme of continual development, please contact CoolLED (<https://www.cooled.com/contact/contact-form/>) for performance data

Control & Interface

Manual:	Dual function remote manual control pod for White/Simple mode or Advanced mode
Remote:	Via USB for independent on/off and intensity control of each channel. Triggering speed <1ms Via 4 TTL inputs for independent on/off control of each channel. Triggering speed <20us Via single TTL for on/off control of manual or software selected channels Via 4 analogue inputs 0-10V, 0-300kHz for dynamic control of intensity from external analogue signals
Synch Out:	4 TTL outputs for each channel – active high 1 TTL output for any channel – active high
Programmable Interface:	4 TTL outputs for on/off control of peripherals (transmitted illuminators, stages etc.) 4 Analogue outputs for intensity control of peripherals (can be programmed to mirror LED intensities for channel control) 0-10V full scale.
Function Generator:	Internally generated sine, pulse and ramps for each channel programmed via control pod.
Connectivity:	USB (B type) for PC connection. All other TTL and Analogue inputs/outputs via 25way 'D-type' female connector (optional rear mounting pE-Expansion Box available for BNC connectivity).
Imaging Software:	Micromanager, MetaMorph, cellSens, NIS Elements, ImagePro, LASX, Zen etc. https://www.cooled.com/product-detail/imaging-software/

To Order

pE-4000-L-SYS-ZZ:	pE-4000 Light Source with manual control pod, and power supply for liquid light guide delivery
pE-4000-F-SYS-ZZ:	pE-4000 Light Source with manual control pod and power supply for fiber delivery
pE-4000-EB25D:	Rear mounting pE-Expansion Box for 25-way D-type to BNC connectivity
pE-4000-EFH-4	Excitation filter holder (4)
pE-1904:	1m long, 3mm diameter liquid light guide
pE-1908:	3m long, 3mm diameter liquid light guide
pE-10400:	Universal collimator for use with a single liquid light guide. Requires microscope adaptor
pE-ADAPTOR-YYY	To customer-specified microscope

A range of fibers is available from CoolLED. See Accessories (<https://www.cooled.com/product-detail/accessories/>)

To specify microscope code (YYY), see Adaptors (<https://www.cooled.com/product-detail/adaptors-new/>)

To specify Power Cable (ZZ): 10 = Australia, 20 = Europe, 30 = UK, 40 = USA

Warranty:	System Warranty: 24 months extendable by product registration. LED Warranty: 36 months
------------------	---

Power

Power requirements:	110-240V a.c. 50/60Hz, 2.5A
Power consumption:	See table under Sustainability

Dimensions

pE-4000 Light Source:	150mm(w) x 220mm(d) x 260mm(h)	Weight 3.5kg
pE-4000 Control pod:	154mm(w) x 135mm(d) x 40mm(h)	Weight 0.95kg
pE-4000 Power Supply:	164mm(w) x 64mm(d) x 35mm(h)	Weight 0.58kg
pE-Expansion Box:	151mm(w) x 18mm(d) x 95mm(h)	Weight 0.34kg

Environment & Safety

- Mercury-free and Laser-free
- Energy Efficient
- Long lifetime (25,000 operating hours)
- No bulb replacements
- Reduced risk of eye damage
- Quiet operation
- No special disposal regulations or issues



For more information on how CoolLED products can help you, contact us now:

t: +44 (0)1264 323040 (Worldwide) 1-800-877-0128 (USA/Canada)
w: www.CoolLED.com
e: info@CoolLED.com

CoolLED
Simply Better Control

www.CoolLED.com

